

CT6E

AC Electric Cargo Tractor

0 5

The Charlatte Model CT6E Cargo Tractor is a self propelled battery powered electric support vehicle designed to tow over 30+ Tons. Power for the main drive is supplied by a 50 hp (37 kw) hi-torque AC motor. The unit has excellent visibility and has a maximum speed of 15.5 mph (25 km/h) when empty. Maximum drawbar capacity is over 6,000 lb (2,800 kg). Options include: Complete cab assembly with heater, defroster, mirrors, wiper, and vinyl doors, Various hitch configurations, Back up alarm, and additional lights.

STANDARD FEATURES

CHARLATTE

- Designed For Lithium Batteries Up To 840 AH
- Highly Maneuverable 141" Turning Radius
- Power Braking System With Brake Booster & Four Rear Brake Calipers For More Stopping Power
- AC Electric Power Steering With Hydraulic Accumulator
- Hi-Torque Low Maintenance AC Drive Motor
- Suspended Footbrake Pedal Automotive Feel
- > Electric PCB For Easier Maintenance



TECHNICAL CHARACTERISTICS

Manufacturer	Manufacturer		Charlatte of America
Model	Manufacturer's Designation		CT6E
Energy Source	Battery (Lithium)	Volts	80
Battery Capacity	Ampere Hour Range (Max)	AH	840
Controller	Manufacturer		Curtis
	High Capacity Controller (900 A) W/Cooling System For Increased DBP		
	80 Volt AC MOSFET controller with CAN buss and serial communication		
Motor	Туре	ha (ha	AC Hi-Torque
	Rating @ 80 Volts	hp / kw	50 / 37
Dimensions	Length	in / mm	136.2 / 3460
	Width	in / mm	60.2 / 1530
	Height with Cab	in / mm	86.6 / 2200
	Outside Turning Radius	in / mm	141 / 3600
Performance	Speed Empty	mph/km/h	15.5 / 25
	Max. Rated Tractive Effort	lb / kg	6000 / 2800
	Gross Vehicle Weight	lb / kg	9612/4360
Chassis	Frame Mfg. W/ Jigs & Fixtures		Yes
	Auto Design Wiring Harness		Yes
	Tires Front		6.00R X 10
	Tires Rear		7.00R X 12
	Wheel Base C/L (E)	in / mm	75.1 / 1910
	Service Brake - Front	Туре	Disc
	Service Brake - Front	Туре	Dual Disc
	Suspension	Front	Leaf Springs
		Rear	Leaf Springs

These descriptions are given as an indication only and do not represent a commitment









Charlatte America

P.O. Box 968 600 Mountain Lane Bluefield, VA 24605 Phone: (276) 326-1510 Fax: (276) 326-1602 e-mail: equipmentsales@charlatteus.com

Charlatte France

Z.I. – Route du Boutoir
89210 Brienon sur Armancon (France)
Phone: (33) 386 43 01 30
Fax: (33) 386 43 04 66 www.CharlatteAmerica.com
e-mail: contact@charlattemanutention.fayat.com

Charlatte United Kingdom

14 Huffwood Trading Estate Brookers Road RH14 9UR Billingshurt, West Sussex United Kingdom Phone: +44 (0) 1403 788897 e-mail: ukparts@charlattemanutention.fayat.com