

# **CWT300E**



The Charlatte Model CWT-300E is an affordable 80V battery powered electric water servicing vehicle. This Low-profile design is perfect for regional jet and narrow-body applications. The unit incorporates a 200 gallon and 100 gallon water (blue juice) tanks. Power is supplied by a 40 hp (30 kw) AC motor which is directly coupled to the heavy-duty Charlatte rear axle. The unit has excellent visibility, maneuverability, and has a maximum speed of 19 mph (30.5 km/h). Options include: On-board charger, Fast Charge port, cold weather package, complete cab assembly with heater, defroster, mirrors, wiper, and vinyl door.

# **STANDARD FEATURES**

- **Ø** Power Steering
- Rugged Design and Construction
- Molded Polyethylene Tanks
- Split Braking System
- ## High Efficiency Low Maintenance AC Tram Motor
- Storage Area in Rear for Cleanup
  Material
- Storage Tray Behind Operator for Equipment

# CWT300E

## **TECHNICAL CHARACTERISTICS**

Manufacturer	Manufacturer		Charlatte of America	
Model	Manufacturer's Designation		CLT-200E	
<b>Energy Source</b>	Battery	Volts	80	
Battery Capacity	Ampere Hour Range	AH	500	
Controller	Manufacturer		Curtis	
	Model		1238	
	80 Volt AC MOSFET controller with CAN buss and serial communication			
Motor	Туре		AC Electric	
	Rating @ 80 Volts	hp / kw	40.0 / 30.0	
	Rating Speed	rpm	1400	
Dimensions	Longth	in / mm	170 0 / 4547	
Dimensions	Length Width	in / mm	179.0 / 4547 57.5 / 1461	
	Height w/o Cab	in / mm	49.0 / 1245	
	Sitting Height		34.0 / 864	
	Outside Turning Radius	in / mm	228.0 / 5791	
	Outside Furfillig Radius	in / mm	228.07 3791	
Performance	Speed Empty	mph/km/h	19 / 30.5	
Chassis	Frame Mfg. W/ Jigs & Fixtures		Yes	
	Auto Design Wiring Harness		Yes	
	Wheels Front/Rear		Heavy Duty One Piece	
	Tires Front		750 X 10	
	Tires Rear		21575R15	
	Wheel Base C/L (E)	in / mm	93.1 / 2365	
	Track Width C/L Front/Rear	in / mm	45.0 / 1143	
	Ground Clearance	in / mm	5.8 / 147	
	Service Brake Front/Rear		Disc/Drum (Bendix)	
	Parking Brake		Rear Drum	
	Suspension	Front	Leaf Springs	
		Rear	Leaf Springs	
			.,	
Drive Axle	Motor Direct Coupled To Axle		Yes	
	Reduction In Differential		Yes	
	Reduction		17.45:1	

200 Gallon Front Water (Blue Juice) Tank			
200 Gallon Capacity	<ul> <li>Molded Polyethylene Material</li> </ul>		
Water Line Reel With Crank Lever	8" Clean Out Cover Located On Top		
<ul> <li>Mounted on 1/2" Pressure Treated Plywood</li> </ul>			

100 Gallon Rear Water (Blue Juice) Tank			
100 Gallon Capacity	Molded Polyethylene Material		
<ul> <li>Plumbed In Series With Front Tank</li> </ul>	8" Clean Out Cover Located On Top		
Mounted on 1/2" Pressure Treated Plywood			

Options Available			
Water Line Space Heater w/Cable Reel	Flow Meter		
• Space Heater – Pump/Plumbing	In Tank Heater		
<ul> <li>Insulation Around Tanks &amp; Plumbing</li> </ul>	On-board Charger		
Fast Charge Port	Complete Cab Assembly		

These descriptions are given as an indication only and do not represent a commitment



#### **Charlatte America**

P.O. Box 968 600 Mountain Lane Bluefield, VA 24605 Phone: (276) 326-1510 Fax: (276) 326-1602

e-mail: equipmentsales@charlatteus.com

#### **Charlatte France**

Z.I. – Route du Boutoir 89210 Brienon sur Armancon (France)

Phone: (33) 386 43 01 30 Fax: (33) 386 43 04 66

e-mail: contact@charlattemanutention.fayat.com

### **Charlatte United Kingdom**

LSUK Building Spindle Way RH10 1TG Crawley West Sussex United Kingdom

Phone: (44) 01 293 529 640

e-mail: ukparts@charlattemanutention.fayat.com